

flexcoat

FLEXIBLE WATERPROOF FOILS


Flexcoat is developed for covering full surface of substract. The most significant feature is strong elasticity with soft touch.

Flexcoat is waterproof and airproof. It is not self-adhesive. Polyurethane based adhesive compatibility is for both textile and leather surfaces.

Total thickness is 19 microns and 4 microns part is transferrable.

Flexcoat is used for leggings with elastic fabrics in textile industry. It is also used in leather industry to have double side skin and increase the quality of skin.

In addition to the transparent foils, more than 20 different color options are available.



MATT BLACK



MATT TRANSPARENT



Application Parameters

Rotopress

Temperature

145-150 °C

Pressure

6 bar

Speed

3-5 m/min

Available Quantities and Sizes

CORE



LENGTH



WIDTH

3" core 200/500/1000 m

150 cm

Customer-specific length can be produced upon request



All foil thicknesses are 19 microns

Conformity

- Applicable for both rotogravure or spray coated adhesive surfaces
- Reverse wash is recommended at 30°C for 50 minutes at gentle washing programme of washing machine
- Not suitable for dry cleaning
- Iron at "one dot" as reverse ironing
- Recommended shelf life is 6 months at dry and cool area



Digital Catalogue



STANDARD 100



19.HTR.97674 Hohenstein HTTI

www.oeko-tex.com

international@uesfoils.com

uesfoils.com @ uesfoils

UES Foils B.V.

UES Makina Tekstil İnşaat ve Gıda San. Tic. Ltd. Şti.

Parellaan 52, 2132 WS Hoofddorp - The NETHERLANDS

Atatürk Mah. Kasırga Sok. No:6/2 Esenyurt - İstanbul - TÜRKİYE

+31 23 785 29 93

+90 212 557 10 40