



## HT Series HIGH TEMPERATURE DURABLE FOILS


HT Series hot stamping foils are developed for better performance.

HT Series are produced to be resistant to 200-210°C heat with its special chemical design. They show better performance, especially when used with plastisol based adhesives.

HT Series have high temperature resistance for stamping at production or ironing later.

HT Series have better wash resistance performance compared to conventional hot stamping foils.

In addition to the clarity foil, more than 20 different color options are available.



### Application Parameters

#### Flat Press

Temperature	Pressure	Contact time
🌡️ 150°C	🕒 6 bar	🕒 5-6 sec

#### Rotopress

Temperature	Pressure	Speed
🌡️ 160°C	🕒 6 bar	🕒 3-5 m/min

### Available Quantities and Sizes

CORE	LENGTH	WIDTH
1" core	100 m	150 cm
3" core	500/1000/3000 m	150 cm

Customer-specific length can be produced upon request

↓ All foil thicknesses are 16 microns

### Conformity

- Water based adhesives
- Plastisol adhesives
- Polyurethane adhesives
- Crystal foil compatibility
- Serigraphy prints
- Roll to roll rotary prints
- Spray applications



Digital Catalogue



STANDARD 100

19.HTR.97674  
Hohenstein HTTI

www.oeko-tex.com

✉ international@uesfoils.com

UES Foils B.V.

Parellaan 52, 2132 WS Hoofddorp - The NETHERLANDS

☎ +31 23 785 29 93

🌐 uesfoils.com

📷 uesfoils

UES Makina Tekstil İnşaat ve Gıda San. Tic. Ltd. Şti.  
Atatürk Mah. Kasırga Sok. No:6/2 Esenyurt - İstanbul - TÜRKİYE

☎ +90 212 557 10 40