

OAFETY DATA OUEET

Revision: 1.0 Form No: AFS-001

SAFETY DATA SHEET

According to Regulation (EU) No 2015/830

TVS-100

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: TVS-100

Product identifier: Solvent based adhesive for hot stamping foil

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Textile and leather printing material

1.3 Details of the supplier of the safety data sheet

Supplier: UES Makina Tekstil İnşaat ve Gıda San. Tic. Ltd. Şti.

Address: Kıraç Atatürk Mh. Kasırga Sk. No:6 Esenyurt/İSTANBUL – TÜRKİYE

Phone: +90 212 557 10 40 Fax: +90 212 557 10 43

E-mail: international@uesvarak.com

1.4 Emergency telephone number

UES Foils: +90 212 557 10 40

Emergency First Aid Center: 112
National Poison Counseling Center: 114
Fire Department: 110

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards
Human health
Flam. Liq. 2-H225
Eye Irrit. 2-H319
STOT SE 3-H336

Environment Not classified.

The Full Text for all Hazard Statements are Displayed in Section 16.

2.2 Label elements

Label In Accordance With (EC) No. 1272/2008



Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/light/equipment.

P242 Use non-sparking tools.



SAFETY DATA SHEET

According to Regulation (EU) No 2015/830

TVS-100

P305 + P351 + P338

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

Revision: 1.0

Form No: AFS-001

2.3 Other hazards

This product does not contain any PBT or vPvB substances.

3. Composition/information on ingredients

3.2 Mixtures

Name	CAS No.	EC No.	Ratio (%)	Classification (T.C. 28848)
Ethyl methyl ketone (MEK)	78-93-3	201-159-0	45-55	Flam. Liq. 2-H225 Eye Irrit. 2-H319 STOT SE 3-H336 EUH066
Polyurethane resin	-	-	45-55	-

4. First aid measures

4.1 Description of first aid measures

General notes

Symptoms may appear after some time has passed since exposure. Consult a doctor with this Safety Data Sheet in case of exposure to the product.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If not breathing, give artificial respiration.

Get medical advice / attention if you feel unwell.

Get medical advice / attention if experiencing respiratory symptoms.

Ingestion

Rinse your mouth with water. Do not induce vomiting.

Get immediate medical advice / attention.

If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

Skin contact

Remove / Take off all contaminated clothing immediately.

Wash with plenty of soap and water.

Get immediate medical advice / attention, if skin irritation or rash occurs.

Eye contact

Whilst protecting yourself, relocate the casualty away from the source of danger.

Remove contact lenses, if present and easy to do. Continue rinsing.

Rinse with clean water for at least 15 minutes and then seek medical attention.

When rinsing, open your eyelids with fingers to insure saturation of water.

4.2 Most important symptoms and effects, both acute and delayed

Acute and delayed effects are noted in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

5. Firefighting measures

5.1 Extinguishing media

Dry extinguishing powder, carbon dioxide, sand, water spray (not splash).

Fight large fire with alcohol resistant foam or water spray.



SAFETY DATA SHEET

According to Regulation (EU) No 2015/830

TVS-100

Revision: 1.0

Form No: AFS-001

5.2 Special hazards arising from the substance or mixture

Combustion products: carbon monoxide (CO), carbon dioxide (CO₂)

Vapors are heavier than air and may spread along floors.

Flammable.

Risk of ignition.

Forms explosive mixtures with air at ambient temperatures.

Pay attention to flashback.

When heated, containers may explode. Thermal decomposition can generate irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Advice for firefighters

Depending on the size of the fire, it may be necessary to use full protective clothing and individual breathing equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit, etc.)

Other informations

In case of accidents and other emergencies, act in accordance with the Internal Emergency Plan and SDS. Eliminate any source of sparks. In the event of fire, cool containers and tanks that are likely to ignite, explode or scorch due to high temperature. Do not allow the products used in fire extinguishing to be poured into the aqueous environment.

Accidental release measures

Personal precautions, protective equipment and emergency procedures 6.1

Shut off all sources of ignition. The use of personal protective equipment is mandatory in case of contact with the spilled product (See section 8). Evacuate the area and keep unprotected persons away. Avoid breathing smoke and gas.

6.2 Environmental precautions

Avoid releasing to the environment. Keep away from drainage, surface and ground water.

6.3 Methods and material for containment and cleaning up

Collect into open container by absorbing with cloths, rags, sand or etc. and then rinse with plenty of water.

Contain the flow path with blankets or sand bags and collect into an appropriate container for large spills.

Prevent the inflow into drains, sewer, basement, or enclosed areas.

Wear appropriate protective equipment throughout the process.

Reference to other sections

See section 13 for waste disposal.

Handling and storage

Precautions for safe handling

Work under hood. Keep away from open flames, hot surfaces and source of ignition.

Take precautionary measures against static discharges. Use only non-sparking tools..

To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded Seal container after use.

Wash hands thoroughly and rinse mouth after handling.

Do not eat, drink or smoke when using this product.

Do not carry contaminated gloves and protective equipment into rest / break areas.

Wear proper protective equipment to avoid inhalation and contact with eyes and skin.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Keep cool and well-ventilated place.

Store in a dark light-safe area.

Do not freeze.

Specific end use(s)

Except for the aforementioned instructions, no recommendations regarding the use of this product are required to be followed.



Revision: 1.0 Form No: AFS-001

SAFETY DATA SHEET

According to Regulation (EU) No 2015/830

TVS-100

Exposure controls/personal protection

Control parameters

Component	European Union
Ethyl methyl ketone (MEK)	TWA: 200 ppm (8h) TWA: 600 mg/m³ (8h) STEL: 300 ppm (15min) STEL: 900 mg/m³ (15min)

Derived No Effect Level (DNEL)

Component	Chronic effects systemic (Dermal)	Chronic effects systemic (Inhalation)
Ethyl methyl ketone (MEK)	DNEL = 1161 mg/kg	DNEL = 600 mg/m ³

Predicted No Effect Concentration (PNEC)

Component	Compartment	Value
Ethyl methyl ketone (MEK)	Fresh water	PNEC= 55,8 mg/L
	Sea water	PNEC= 55,8 mg/L
	Fresh water sediment	PNEC= 284,74 mg/kg
	Sea sediment	PNEC= 287,7 mg/kg
	Soil	PNEC= 22,5 mg/kg

Exposure controls Protective equipment









Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Body Protection

Wearing flame retardant protective clothes (long sleeve uniform) that organic solvent or the chemical do not infiltrate easily is preferred.

Respiratory equipment

Wearing organic vapor gas mask is preferred. Recommended Filter type: Filter A (acc. to DIN 3181)

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental Exposure Controls

No data available.



SAFETY DATA SHEET

According to Regulation (EU) No 2015/830

TVS-100

Revision: 1.0 Form No: AFS-001

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Liquid

Colour Slightly yellow Odour Characteristic Solubility No data available. Approx. 80 °C Firts boiling point No data available. Vapor pressure No data available. Melting point No data available. Density No data available. Dynamic viscosity No data available. Kinematic viscosity

Concentration 48-55%

рΗ No data available. No data available. Vapor density Partition Coefficient No data available. (N-Octanol/Water) No data available. Decomposition temperature Flammability Highly flammable -7 °C (closed cup) Flash point Lower: 1.8 Vol% **Explosion limits** Upper: 11.5 Vol% Autoignition temperature No data available.

9.2 Other information

No data available.

10. Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

Stable under normal temperature conditions and recommended use. Stable under prescribed storage conditions.

10.3 Possibility of hazardous reactions

Generation of peroxide may occur in contact with air, light or oxidizing agents.

Risk of explosion in contact with: hydrogen peroxide/nitric acid or hydrogen peroxide/sulfuric acid.

Electrostatic charging possible. The substance can react dangerously with: oxidizing agents, trichloromethane/alkali chromium trioxide.

10.4 Conditions to avoid

Sunlight, heat, open flame, high temperature, sparks, static electricity, other sources of ignition.

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) gas might be generated by combustion.



Revision Date: 03.06.2024

Revision: 1.0 Issue Date: 05.02.2024 Form No: AFS-001

SAFETY DATA SHEET

According to Regulation (EU) No 2015/830

TVS-100

Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
	(Rat)	(Rabbit)	(Mouse-4h)
Ethyl methyl ketone (MEK)	2740 mg/kg	6480 mg/kg	32000 mg/m ³

Skin corrosion/irritation

No data available.

Serious eye damage/eye irritation

Eye Irrit. 2-H319

Respiratory or skin sensitization

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

Specific target organ toxicity - single exposure

STOT SE 3-H336

Specific target organ toxicity - repeated exposure

No data available.

Aspiration hazard

No data available.

Additional information 11.2

No data available.

Ecological information

12.1 **Toxicity**

Component	LC50 Fish (96 h)	EC50 Crustaceans (48 h)
Ethyl methyl ketone (MEK)	3220 mg/kg (Pimephales promelas)	5090 mg/kg (Daphnia magna)

12.2 Persistence and degradability

Component	Degradability
Ethyl methyl ketone (MEK)	98% (28d)
Polyurethane resin	No data available



ssue Date: 05.02.2024

SAFETY DATA SHEET
According to Regulation (EU) No 2015/830

TVS-100

Revision: 1.0

Form No: AFS-001

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

The product does not meet the PBT and vPvB criteria.

12.6 Other adverse effects

No data available.

13. Disposal considerations

13.1 Waste treatment methods

The product must be disposed of in accordance with official regulations. Do not allow the product to mix into sewers and groundwater.

14. Transport information

14.1 UN Number

ADR/RID: 1866 IMDG: 1866 IATA: 1866

14.2 UN proper shipping name

ADR/RID: RESIN SOLUTION, falmmable IMDG: RESIN SOLUTION, falmmable RESIN SOLUTION, falmmable

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3



14.4 Packing group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6 Special precautions for user

No special precautions required.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out.



Revision: 1.0 Form No: AFS-001

SAFETY DATA SHEET

According to Regulation (EU) No 2015/830

TVS-100

Other information 16.

Abbreviations

CAS: Chemical Abstracts Service.

European Inventory of Existing Commercial Chemical Substances (EINECS). EC:

TWA: Time Weighted Average. STEL: Short Term Exposure Limit. Derived No Effect Level. DNEL:

PNEC: Predicted No Effect Concentration.

Lethal Dose, 50% LD50:

LC50: Lethal Concentration, 50% EC50: Effective Concentration, 50%

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association.

MARPOL: International Convention for the Prevention of Pollution From Ships.

Intermediate Bulk Container- International Code for the Construction and Equipment IBC:

PBT: Persistent, Bioaccumulative and Toxic vPvB: Very Persistent and Very Bioaccumulative

Classification procedures

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/light/equipment.

P242 Use non-sparking tools.

P305 + P351 + P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present

and easy to do. Continue rinsing.

Revision Comments

Revised according to CLP Regulation.

The concentration value changed. 2.0

Serhat Gündüz Issued By: **Certificate No:** KDU01.24.06 **Certificate Validity Date:** 27.08.2027 issue Date: 05.02.2024 Revision: 1.0 **Revision Date:** 03.06.2024

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.